

HUBER+SUHNER® DATA SHEET

Coaxial Cable: RG_178_B/U



Description

PTFE - 50 Ohm - single screen

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.31 mm
Dielectric	PTFE		0.83 mm
Outer conductor	Copper, Silver plated	Braid, 95 %	1.33 mm
Jacket	FEP	RAL 8015 - br	1.8 mm +/- 0.1
Print	HUBER+SUHNER RG 178 B/U 50 Ohm (PA no.)		

Electrical Data

Impedance	50	Ω +/- 2
Max. operating frequency	1	GHz
Capacitance	97	pF/m
Velocity of signal propagation	69	%
Signal delay	4.84	ns/m
Insulation resistance	$\geq 1 \times$	$10^8 \text{ M}\Omega\text{m}$
Min. screening effectiveness	>40	dB (up to 1 GHz)
Max. operating voltage	0.5	kV _{rms} (at sea level)
Test voltage	1	kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	0.84	kg/100 m
Min. bending radius	static	10 mm
	repeated (for max. 50 bendings)	18 mm
	dynamic	27 mm

Environmental Data

Temperature range	-20 °C... + 60 °C	-65 °C... + 165 °C
Installation temperature	-20 °C... + 60 °C	
Flammability	IEC 60332-3	
2002/95/EC (RoHS)	compliant	

Ordering Information

Order as RG_178_B/U

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Cable group U1 1 mm / 50 Ohm

HUBER+SUHNER® DATA SHEET

Coaxial Cable: RG_178_B/U



Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] and **Power CW** [formula: $(p \cdot f^{0.5})$]

Coefficients:

a=	1.4135	b=	0.2038	f _{max} =	1	p _{at} 1GHz =	59
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.05		0.33		0.101		264
	0.10		0.47		0.143		187
	0.15		0.58		0.177		152
	0.20		0.67		0.204		132
	0.25		0.76		0.232		118
	0.30		0.84		0.256		108
	0.35		0.91		0.277		100
	0.40		0.98		0.299		93
	0.45		1.04		0.317		88
	0.50		1.10		0.335		83
	0.55		1.16		0.354		80
	0.60		1.22		0.372		76
	0.65		1.27		0.387		73
	0.70		1.33		0.405		71
	0.75		1.38		0.421		68
	0.80		1.43		0.436		66
	0.85		1.48		0.451		64
	0.90		1.52		0.463		62
	0.95		1.57		0.479		61
	1.00		1.62		0.494		59

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
 www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions