## **HUBER+SUHNER® DATA SHEET**Coaxial PCB Connector: 85 QMA-50-0-3/111 N



## Description

Right angle PCB jack

Interface Standards QMA QLF compliant



## **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & \quad \text{50 } \Omega \\ \text{Interface frequency max.} & \quad \text{6 GHz} \\ \end{array}$ 

**Mechanical Data** 

Board mounting type through holes Weight 0.0041 kg

**Environmental Data** 

Operating Temperature -40 °C to 85 °C 2002/95/EC (RoHS) compliant

**Material Data** 

Piece PartsMaterialCentre contactCopper Beryllium / BronzeOuter contactBrassBodyBrassInsulatorPFA / PTFE

**Related Documents** 

Outline drawing DOU-00012659
Catalogue drawing DCA-00012661
Mounting hole DOU-00002524

Ordering Information

Bulk 100 pcs package 85\_QMA-50-0-3/111\_NH

**Surface Plating** 

SUCOPRO Plating SUCOPRO Plating SUCOPRO Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions** 

HUBER+SUHNER
HUBER+SUHNER AG

RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com

Document: DOC-0000192749 G Issued: 06.11.07 Uncontrolled Copy Page 1/1